

B/W Multifunction Printer

# SP 4510SF

✓ Copier ✓ Printer ✓ Facsimile ✓ Scanner



SP 4510SF

40  
ppm B/W

# SP 4510SF

## MAIN SPECIFICATIONS

### GENERAL

Warm-up time:	19 seconds
First output speed:	6 seconds
Continuous output speed:	40 pages per minute
Duty cycle:	150,000 prints per month
Dimensions (W x D x H):	419 x 427 x 484 mm
Weight:	23 kg
Power source:	220 - 240 V, 50/60 Hz

### COPIER

Copying process:	Dry, single component & electro-photographic printing
Multiple copying:	Up to 99 copies
Resolution:	600 x 600 dpi
Zoom:	From 25% to 400% in 1% steps

### PRINTER

RAM:	Standard: 1,024 MB Maximum: 1,536 MB
Printer language:	Standard: PCL5e, PCL6, Adobe® PostScript® 3™ Option: XPS
Print resolution:	1,200 x 1,200 dpi
Interface:	Standard: USB 2.0, SD slot, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth
Network protocol:	TCP/IP (IP v4, IP v6), IPX/SPX (Option)
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® 8, Windows® 8.1, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012, Windows® Server 2012R2
Mac OS environments:	Macintosh OS X v10.5 or later
UNIX environments:	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX
Novell® Netware® environments:	v6.5 or later
SAP® R/3® environments:	SAP® R/3 3.x® or later

### SCANNER

Scanning speed:	Full colour: Maximum 30 originals per minute B/W: Maximum 30 originals per minute
Resolution:	Standard: 100 - 600 dpi
File format:	Single page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF-A
Bundled drivers:	Network TWAIN
Scan to:	E-mail, Folder, USB, SD card, SMB, FTP, NCP (Option)

### FAX

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Transmission speed:	G3: 2 second(s)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2.4 second(s)
Memory capacity:	Standard: 4 MB
Memory backup:	Yes: 12 hour

### PAPER HANDLING

Recommended paper size:	Standard paper tray(s): A4, A5, A6, B5, B6, Legal, Letter, Executive, Foolscape, Folio, 16 KAI Bypass tray: A4, A5, A6, B5, B6, Legal, Letter, Executive, Foolscape, Folio, 16 KAI
Paper input capacity:	Standard: 600 sheets Maximum: 1,600 sheets
Paper output capacity:	Maximum: 250 sheets
Paper weight:	Standard paper tray(s): 52 - 162 g/m² Optional paper tray(s): 52 - 162 g/m² Bypass tray: 52 - 162 g/m² Duplex: 52 - 162 g/m²

### ECOLOGY

Power consumption:	Maximum: 1.1 kW Ready mode: 97.2 W Sleep mode: 0.72 W TEC (Typical Electricity Consumption): 1,759 Wh
--------------------	--

### SOFTWARE

Standard:	SmartDeviceMonitor, Web SmartDeviceMonitor®, Web Image Monitor
Optional:	GlobalScan NX, Streamline NX, Document Manager NX, Card Authentication Package, Unicode Font Package for SAP

### OPTIONS

Paper tray (1 x 250-sheet paper tray, 1 x 500-sheet paper tray), Medium cabinet, High cabinet, Hard Disk Drive (320 GB), RAM (1.5 GB), Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, VM Card, Netware, Browser unit, Counter interface, File format converter, Copy Data Security Unit, Unicode Font Package for SAP, OCR Unit, XPS direct print

### CONSUMABLES

Starter toner:	Black: 6,000 prints
PCU yield:	Black: 20,000 prints
Toner cartridge (regular yield):	Black: 3,000 prints
Toner cartridge (high yield):	Black: 6,000 prints
Toner cartridge (ultra high yield):	Black: 12,000 prints

*For availability of models, options and software, please consult your local Gestetner supplier.*



**Gestetner**

[www.gestetner.com](http://www.gestetner.com)

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2014 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.