

Aficio®

**MP 301SP
MP 301SPF**

Desktop Digital Multi Function Printer

☑ Copier ☑ Printer ☑ Facsimile ☑ Scanner



**Aficio™ MP
301SP**



B/W

**Aficio™ MP
301SPF**



B/W

MP 301SP/MP 301SPF

MAIN SPECIFICATIONS

Aficio®

GENERAL

Warm-up time:	23 seconds
First output speed:	6 seconds
Continuous output speed:	30 pages per minute
Dimensions (W x D x H):	476 x 450 x 451 mm
Weight:	26 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	Laser beam scanning and electro-photographic printing
Multiple copying:	Up to 99 copies
Resolution:	600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

RAM:	Maximum: 1,024 MB
HDD (Option):	Maximum: 128 GB
Printer language:	Standard: PCL5e, PCL6, XPS, Adobe® PostScript® 3™
Interface:	Standard: USB 2.0, Ethernet 10 base-T/100 base-TX Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet
Network protocol:	TCP/IP, IPX/SPX (Option)
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008
Mac OS environments:	Macintosh OS X Native v10.2 or later
UNIX environments:	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3 3.x® or later

SCANNER

Scanning speed:	Full colour: Maximum 30 originals per minute B/W: Maximum 30 originals per minute
Resolution:	Standard: 100 - 600 dpi
File format:	Single page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF-A
Scan to:	E-mail: SMTP, TCP/IP Folder: SMB, FTP, NCP (Option)

FAX

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2.4 second(s)
Memory capacity:	4 MB
Memory backup:	Yes

PAPER HANDLING

Recommended paper size:	Standard paper tray(s): A4, A5 Bypass tray: A4, A6
Paper input capacity:	Maximum: 1,350 sheets
Paper output capacity:	Standard: 250 sheets
Paper weight:	Standard paper trays: 60 - 90 g/m² Bypass tray: 60 - 157 g/m² Duplex tray: 64 - 90 g/m²

ECOLOGY

Power consumption:	Maximum: W1.1 kW Operating power: B/W copy (450 W, kW)Colour copy (W, kW)B/W print (W, kW)Colour print (W, kW)Scan (W, kW) Full option maximum power: 1,100 W kW Ready mode: 83.5 W Low power mode: W kW Sleep mode: Power (3.1 W, kW)Default Timer setting (min.)Timer (- 1 min.)Recovery (1 sec.) TEC (Typical Electricity Consumption): 1,535 W/h kW/h Plug-in: Power (W, kW)Recovery (sec.) Panel off (level 2) timer: Power (W, kW)Default Timer setting (min.)Timer (- min.)Recovery (sec.) Energy Saver timer: Power (W, kW)Default Timer setting (min.)Timer (- min.)Recovery (sec.) ES Ceiling: W kW ES Efficiency: W kW Heat emission: kcal/h
--------------------	---

OPTIONS

Platen cover, ARDF, 2 x 500-sheet paper tray, Hard Disk Drive, Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet, VM Card, Netware, Pictbridge, Browser unit, Counter interface, File format converter, Copy Data Security Unit, Fax board

Warm-up time: 30 seconds from power off, 10 seconds from sleep mode.

Up to 2 optional 500-sheet paper trays can be attached.

For availability of models, options and software, please consult your local Gestetner supplier.



ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2012 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.gestetner.com

Gestetner