

MP C6502SP MP C8002SP

Digital Colour Multi Function Printer

☑ Copier ☑ Printer ☑ Facsimile ☑ scanner



MP C6502SP

65 ppm B/W Colour

MP C8002SP

80 ppm B/W Colour

MP C6502SP/MP C8002SP

MP C6502SP/MP C8002SP

GENERAL

Warm-up time:	45 seconds
First output speed:	Full colour: 7.2/6.2 seconds B/W: 5.3/4.6 seconds
Continuous output speed:	Full colour: 65/80 pages per minute B/W: 65/80 pages per minute
Memory:	Standard: 2.5 GB
HDD:	640 GB
Dimensions (W x D x H):	750 x 880 x 1,225 mm
Weight:	241 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	4-Drum Dry Electrostatic Transfer System with internal transfer belt
Multiple copying:	Up to 9,999 copies
Resolution:	600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

Printer language:	Standard: PCL5c, PCL6, XPS, PDF, PDF direct print, Mediaprint (JPEG/TIFF) Option: Adobe® PostScript® 3™, IPDS
Print resolution:	1,200 x 4,800 dpi
Interface:	Standard: USB 2.0, SD slot, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth
Network protocol:	TCP/IP (IP v4, IP v6), IPX/SPX (Option)
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® 8, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012
Mac OS environments:	Macintosh OS X v10.2 or later
UNIX environments:	UNIX Sun® Solaris HP-UX SCO OpenServer RedHat® Linux Enterprise IBM® AIX
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3®
Other supported environments:	NDPS Gateway AS/400® using OS/400 Host Print Transform

SCANNER

Scanning speed:	Full colour: Maximum 120 originals per minute B/W: Maximum 120 originals per minute
Resolution:	Maximum: 600 dpi
Original size:	A3, A4, A5, B4, B5
Bundled drivers:	Network TWAIN
Scan to:	E-mail (SMTP, POP, IMAP4), Folder, USB, SD card, SMB, FTP, NCP

FAX

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3, Additional G3 (option)
Resolution:	8 x 3.85 line/mm, 200 x 100 dpi 8 x 7.7 line/mm, 200 x 200 dpi 8 x 15.4 line/mm, 400 x 400 dpi (Option) 16 x 15.4 line/mm, 400 x 400 dpi (Option)
Transmission speed:	G3: 2 second(s)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2 second(s)
Memory capacity:	Standard: 4 MB Maximum: 28 MB

PAPER HANDLING

Recommended paper size:	SRA3+, A3, A4, A5, A6, B4, B5, B6
Paper input capacity:	Maximum: 8,100 sheets
Paper output capacity:	Maximum: 3,500 sheets
Paper weight:	Standard paper tray(s): 52.3 - 256 g/m ² Bypass tray: 52.3 - 300 g/m ²

ECOLOGY

Power consumption:	Maximum: 2,400 W Ready mode: 450 W Low power mode: 196.9/199.3 W Sleep mode: 0.68 W TEC (Typical Electricity Consumption): 5.06/6.48 kWh
--------------------	--

SOFTWARE

Standard:	Web SmartDeviceMonitor®, Web Image Monitor
Optional:	GlobalScan NX, Streamline NX, Card Authentication Package, Unicode Font Package for SAP, Equitrac PCC V4

OPTIONS

2,200-sheet large capacity tray, 4,400-sheet large capacity tray, 3,000-sheet finisher, 2,000-sheet booklet finisher, Punch kits, 9-bin mailbox, Cover interposer, Tab sheet unit, Copy tray, Jogger unit, Copy Connect Kit, Plockmatic Booklet maker, Bi-directional IEEE 1284, Bluetooth, Netware, PostScript3, IPDS unit, Browser unit, Counter interface, File format converter, Data Overwrite Security Unit (Certified version), Copy Data Security Unit, Fax Connection Unit, 2nd Super G3 port, Fax memory, Fax option, Multi folding unit, Unicode Font Package for SAP, Wireless LAN (IEEE 802.11a/g/n), OCR Unit, Cooling Fan Unit, Smart Card Reader Built-in Unit, GBC StreamPunch Pro

CONSUMABLES

Toner capacity:	Black: 48,500 prints Cyan: 29,000 prints Magenta: 29,000 prints Yellow: 29,000 prints
-----------------	--

For availability of models, options and software, please consult your local Gestetner supplier.



ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2013 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.gestetner.com